

IMRON® MARINE 3919S Prepsol

Description

Slow solvent mixture developed for removal of heavy contaminants prior to surface preparation. Composition based on aromatic and aliphatic solvents.

Products

3919S Prepsol

Properties

- Eliminates non-water soluble contaminants, such as wax, polish, tar, silicones and grease from old finishes.

Application - remarks

- Clean surface with water and soap.
- Degrease the area to be repaired with 3919S.
- Wipe dry with clean cloth.
- Never let 3919S evaporate from the surface. Treat only one small area at the time.
- Change cloths often, never use dirty clothes. It is important to thoroughly clean the surface before any sanding operation. Sanding would grind the contaminants into the surface.

RECOMMENDED USE

Products	Packages (l)	Shelf life at 20°C (year)	VOC (g/l) ± 5	Density (kg/l) ± 0.01	Flash Point (°C)
3919S	5 - 20	2	809	0.81	35



IMRON® MARINE 3919S Prepsol

Safety

Consult Material Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

Information

The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Axalta cannot anticipate all variations in actual end-use conditions Axalta makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights.

This Technical Data Sheet supersedes all previous issues.

Copyright 2014, Axalta Coating Systems, LLC and all affiliates. The Axalta logo, Axalta™, Axalta Coating Systems™ and all products denoted with™ or® are trademarks or registered trademarks of Axalta Coating Systems, LLC and its affiliates. Axalta trademarks may not be used in connection with any product or service that is not an Axalta product or service.