

TECHNICAL DATA SHEET

Product Type : **LACQUER**

Product Reference : **LP02W-19182**

Product Name : **LAQUE PU NOIRE BRILLANTE**

Hardener : **TH0759 at 50% in volume**

Description

Two component solvent-based lacquer based on polyurethane resins. It is suitable for indoor application and outdoor application whenever the exposure is low.

Application substrates : PU primer, polyester or PMMA.

Apply on a clean and sanded substrate.

Physical Properties (at 20°C)

Physical properties	
Gloss	B95 +/- 3 gloss unit
Density	0,992 +/-0.03

Instructions for use

Substrate preparation :	Sanding with Jex sponge / Degreasing
Hardener :	TH0759 at 50% in volume
Thinner :	DV9955 at 10-40% in volume
Application method :	Pneumatic gun
Recommended thickness :	60-120 g/m ² per layer
Equipment cleaning :	DV9955

Performances

Dust free :	30 min
Touch dry :	1h
Can be handled after :	/
Can be recovered after :	/



Hard : 24h
Complete crosslinking : /

Those results are indicated for air drying.

Theoretical yield	200-250 g/m ² per layer
--------------------------	------------------------------------

Packaging	1L / 5L / 10L / 25L drum
------------------	--------------------------

Storage

Store at a temperature below 25°C in a dry and well ventilated place away from any source of ignition.
After a long storage time check the product homogeneity and shake well before use.
Shelf life : 6 months in closed packaging.

Hygiene / Safety

Respect the precaution of use by reading the material safety data sheet.

The information given in this data sheet is intended to inform and advise you, to the best of our knowledge, but under no circumstances should we be held liable. The indications do not give rise to our responsibility even in respect of industrial property rights belonging to third parties. The quality of our products is guaranteed under our general conditions of sale. It is up to the user to obtain from our services the most recent edition of the data sheets.

